

**Tile Ventilator Range - Interlocking Plain Tile**

CODE GTV-IP

**Description**

The interlocking plain tile ventilator is designed to provide a quick and simple solution to the problems of roofspace ventilation and mechanical extraction / soil stack termination through a roof covered with small format interlocking plain tiles.

Designed to suit all 3 styles of interlocking plain tiles, the vent is adaptable to be used with the different coverage widths available by simply sliding the top section into the required position for your tile.

The curved, in-line profile helps to maintain an unbroken appearance to the roofline at high or low level with a range of colours available to suit varying roof styles.

The tortured path through the internal weathering geometry is designed to maintain a constant airflow gap of 6,000mm<sup>2</sup> whilst channelling any water ingress out of the vent and on to the roof covering below, with the 4mm louvred grill in place to prevent the entry of debris and large nesting insects.

When using the vent for mechanical extraction or soil stack / vent pipe termination, a 4" pipe adaptor can be fitted to the vent to connect to one of the GRPA Flexible Pipe range.

For more detailed fitting instructions see MBP-1105.

**Weight**

1.006kg

**Box Qty**

6 (6.12kg per box)

**Material**

PVC

**Colours**

Terracotta, Grey, Brown &amp; Antique Red

**Manufacturing**


Injection Moulded

**Free Airflow**

 6,000 mm<sup>2</sup> per unit

**Features**

- Innovative, patented tile vent design.
- Curved, in-line and discreet profile.
- Range of colours available.
- Suitable for all interlocking concrete plain tiles.
- Vent profile suits all top manufacturers tiles.
- Independently wind tunnel tested.
- No batten cutting required.
- Base outlet feeds directly into roof space.
- 4" pipe adaptor available for mechanical extraction.
- Suitable for use down to a 22.5° roof pitch.
- Provides a 4mm louvred flyscreen grill.



MANTHORPE BUILDING PRODUCTS LTD  
 MANTHORPE HOUSE  
 BRITAIN DRIVE  
 CODNOR GATE BUSINESS PARK  
 RIPLEY  
 DERBYSHIRE DE5 3ND

TEL: 01773 303 000  
 FAX: 01773 303 300  
 EMAIL:  
 mbp.care@manthorpebp.co.uk  
 WEB  
 www.manthorpebp.co.uk

DRN B.H. Date 20.06.19

The company maintains a policy  
 of continuous development of its  
 product range and reserves the  
 right to amend the specification  
 without notice.

DRG No

**MBP 8333**




Issue

**C**

1 of 2

## Tile Ventilator Range - Interlocking Plain Tile

CODE GTV-IP




Required Ventilation	Vent Spacing
5,000 mm <sup>2</sup> /m	Install at 1.2m centres
10,000 mm <sup>2</sup> /m	Install at 0.6m centres
25,000 mm <sup>2</sup> /m	Install at 0.24m centres

## References

BSI: BS 5250:2011 Control of Condensation in Building  
BSI: BS 5534:2014 Code of Practice for Slate and Tiling  
BSI: BS 490:2004 Concrete tiles and fittings for roof covering  
BRE: prEN 15601  
Building Regulations 2010  
NHBC: Good Craftsmanship Guides

## Tile Compatibility


## Vent Position A



**Coverage Width:**  
300mm

**For use with:**  
Marley Ashmore  
Redland DuoPlain

## Vent Position B



**Coverage Width:**  
312mm

**For use with:**  
Forticrete Gemini

## Installation Overview

The vent is laid in a broken bond format, taking the place of single tile with no need to cut the tiling battens.

The vent should not be installed on a roof pitch below 22.5 degrees.

MANTHORPE BUILDING PRODUCTS LTD  
MANTHORPE HOUSE  
BRITTAIN DRIVE  
CODNOR GATE BUSINESS PARK  
RIPLEY  
DERBYSHIRE DE5 3ND

TEL: 01773 303 000  
FAX: 01773 303 300  
EMAIL:  
mbp.care@manthorpebp.co.uk  
WEB  
www.manthorpebp.co.uk

DRN B.H. Date 20.06.19

The company maintains a policy of continuous development of its product range and reserves the right to amend the specification without notice.

DRG No

**MBP 8333**

Issue

**C**  
2 of 2