Manthorpe Building Products

0

0

0

B+48

33

В

Product Information Sheet

One Hour Fire Rated Access Panels

A+48

0

A

Code: GL150F Standard


GL130F Standard

GL450F Standard

GL151F Lockable

GL131F Lockable





Description:

0

Manthorpes' range of fire rated access panels provide various sizes of protected openings in ceilings and walls for access to building engineering services such as:

0

Г

Electrical Wiring Systems Fuse Boxes / Switches Controls / Connection Links Valves / Stopcocks / Plumbing

Each fire rated acces panel includes a 'Square Lock & Key' to restrict unwanted access and is fire rated for up to 1 hour. The door is finished in powder coated white and can be over painted to blend with the surrounding surface.

The fire rated panel is a high quality, robust solution suitable for everyday use with all the discrete advantages required of an access panel.

The GL151F, GL131F and GL451F fire rated doors come complete with a cam lock and a set of keys for additional security.

Dimension Table:		
Product Code:	A (mm)	B (mm)
GL150F / GL151F	200	150
GL130F / GL131F	300	300
GL450F / GL451F	450	450

Specification:			
Packing Details	Individually Packaged in Cardboard Box		
Materials	Zintec Mild Steel finished in Polyester Powder Coating (White)		
Seal	PVC Foam		
Insulation	Mineral Fibre (@30mm depth)		
Weights	GL150F, GL151F - 1.2kg GL130F, GL131F - 2.2kg GL450F, GL451F - 4.1kg		
Fire Assessment	WFRC No 516268		

MANTHORPE BUILDING PRODUCTS LTD MANTHORPE HOUSE	TEL: 01773 303 000 FAX: 01773 303 300	Drawn MR 01.03.07	Issue Drawn BH 08.07.25	DRG No	Issue
BRITTAIN DRIVE CODNOR GATE BUSINESS PARK RIPLEY DERBYSHIRE DE5 3ND	EMAIL: mbp.care@manthorpebp.co.uk WEB: www.manthorpebp.co.uk	of continuous d product range a	naintains a policy evelopment of its and reserves the the specification	MBP 8223	08